

Directive EU 65/2014 – EN61591, EN60704-2-13, EN50564		
Brand	SILVERLINE	
Model	SL 4142-60 RF MELIN ADA	
Annual Energy Consumption (AEC)(kWh/a)	38	
Energy Efficiency Class (EEI)	A+	
Fluid Dynamic Efficiency(FDE)	32,7	
Fluid Dynamic Efficiency class (FDE) (Indice)	A	
Light Efficiency (LE)	67	
Lighting Efficiency Class (LE)(indice)	A	
Grease Filtering Efficiency (GFE)	78,3	
Grease Filtering Efficiency Class (GFE)(indice)	C	
Minimum Air Flow in Normal Use MIN (m³/h)	246	
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h)	596	
Air Flow at Intensive/Boost Setting (m³/h)	-	
Sound Power Level at Minimum Speed Available in Normal Use MIN (LWA)(dB)	50	
Sound Power Level at Maximum Speed Available in Normal Use MAX (LWA)(dB)	69	
Sound Power Level at Intensive/Boost Setting (LWA)(dB)	-	
Power Consupcion Off Mode (Po)(W)	0,37	
Power Consupcion in Standby Mode (Ps)(W)	-	
Product Information compliant to commission regulation (EU) No 66/2014		
Time increase factor (f)	0,8	
Energy Efficiency (EElhood)	45,0	
Measured air flow rate at best efficiency point (QBEP)(m³/h)	302,7	
Measured air pressure at best efficiency point (PBEP)(Pa)	479	
Measured electric power input at best efficiency point (WBEP)(W)	123,1	
Nominal power of the lighting system (WL)(W)	3,0	
Average illumination of the lighting system on the cooking surface (Emiddle)(lux)	200	