Directive EU 65/2014 – EN61591, EN60704-2-13, EN50564	
Brand	**SILVERLINE**
Model	**SL 4240-60 RF DIAMOND ADA**
Annual Energy Consumption (AEC)(kWh/a)	**40**
Energy Efficiency Class (EEI)	**A**
Fluid Dynamic Efficiency(FDE)	**33,1**
Fluid Dynamic Efficiency class (FDE) (Indice)	**A**
Light Efficiency (LE)	**50**
Lighting Efficiency Class (LE)(indice)	**A**
Grease Filtering Efficiency (GFE)	**76,1**
Grease Filtering Efficiency Class (GFE)(indice)	**C**
Minimum Air Flow in Normal Use MIN (m^3/h)	**265**
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m^3/h)	**618**
Air Flow at Intensive/Boost Setting (m^3/h)	**-**
Sound Power Level at Minimum Speed Avaible in Normal Use MIN (L_{WA})(dB)	**56**
Sound Power Level at Maximum Speed Avaible in Normal Use MAX (L_{WA})(dB)	**68**
Sound Power Level at Intensive/Boost Setting (L_{WA})(dB)	**-**
Power Consuption Off Mode (Po)(W)	**0,36**
Power Consuption in Standby Mode (Ps)(W)	**-**
Product Information compliant to commission regulation (EU) No 66/2014	
Time increase factor (f)	**0,8**
Energy Efficiency (EElhood)	**45,4**
Measured air flow rate at best efficiency point (Q_{BEP})(m^3/h)	**337,0**
Measured air pressure at best efficiency point (P_{BEP})(Pa)	**460**
Measured electric power input at best efficiency point (W_{BEP})(W)	**130,0**
Nominal power of the lighting system (W_L)(W)	**3,0**
Average illumination of the lighting system on the cooking surface (Emiddle)(lux)	**149**

4240.6.480.04